

Optra M410 Print Cartridge

Printer: Optra M410

Declaration of Yield: **Average Cartridge Yield 10000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 13492
Std Dev 751
90% Lower Confidence 13103

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

start **stop**
Date tested 30-Nov-2004 5-Dec-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At fade 2nd shake At fade
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	7.4.1
Operating system	Windows 2000
Application software	Adobe Acrobat version 6.01
Test page version	IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity				
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min	Cartridge Yield	Cart used in Calculation
CAZ032340231	2546161	74	75	74	48	48	47	14,601	Y
CAZ041250076	2546164	74	75	74	48	48	47	13,734	Y
CAZ041820566	2546156	74	75	74	48	48	47	14,381	Y
CAZ041969099	2546499	74	75	74	48	48	47	13,398	Y
CAZ041969086	2546161	74	75	74	48	48	48	12,082	Y
CAZ032340239	2546164	74	75	74	48	48	48	13,375	Y
CAZ041250099	2546156	74	75	74	48	48	48	13,526	Y
CAZ041820597	2546499	74	75	74	48	48	48	13,426	Y
CAZ041820608	2546161	74	75	74	48	48	48	13,743	Y
CAZ041969090	2546164	74	75	74	48	48	48	12,895	Y
CAZ032340252	2546156	74	75	74	48	48	48	14,282	Y
CAZ041250096	2546499	74	75	74	48	48	48	12,461	Y

Comments and or exceptions:

