

**E230, E232, E330 Print Cartridge**

Printer: E230

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>2500</b>	<b>standard pages</b>
<b>Declared yield value in accordance with ISO/IEC 19752</b>			

**Average** 2843  
**Std Dev** 145  
**90% Lower Confidence** 2768

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
<b>Date tested</b>	11-Jan-2005	12-Jan-2005
Number of cartridges in testing		12
Qty. of cartridges used in calculation		12
Shake Procedure	1st shake	At fade
	2nd shake	At fade
Print mode		Continuous
Number of printers tested		4
Media used		Boise Cascade X-9 - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		9.3
Operating system		Windows 2000
Application software		Adobe Acrobat version 6.01
Test page version		IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAX043484242	38055MP	74	74	74	50	51	50	2,971	Y
CAX043502784	38055MH	74	74	74	50	51	50	3,036	Y
CAX043502780	38055BO	74	74	74	50	51	50	3,003	Y
CAX043513480	380559C	74	74	74	50	51	50	2,861	Y
CAX043513501	38055MP	74	74	74	50	51	50	2,619	Y
CAX043484299	38055MH	74	74	74	50	51	50	2,895	Y
CAX043502659	38055BO	74	74	74	50	51	50	2,643	Y
CAX043502736	380559C	74	74	74	50	51	50	2,954	Y
CAX043502719	38055MP	74	74	74	50	51	50	2,732	Y
CAX043512736	38055MH	74	74	74	50	51	50	2,733	Y
CAX043484303	38055BO	74	74	74	50	51	50	2,944	Y
CAX043502733	380559C	74	74	74	50	51	50	2,727	Y

**Comments and or exceptions:**