

E230, E232, E330 Print Cartridge

Printer: E232

Declaration of Yield:	Average Cartridge Yield	2500	standard pages
Declared yield value in accordance with ISO/IEC 19752			

Average 2919
Std Dev 163
90% Lower Confidence 2834

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	11-Jan-2005	12-Jan-2005
Number of cartridges in testing		12
Qty. of cartridges used in calculation		12
Shake Procedure	1st shake	At fade
	2nd shake	At fade
Print mode		Continuous
Number of printers tested		4
Media used		Boise Cascade X-9 - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		9.3
Operating system		Windows 2000
Application software		Adobe Acrobat version 6.01
Test page version		IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAX043484311	38058XW	74	74	74	50	51	50	3,156	Y
CAX043502725	3804283	74	74	74	50	51	50	2,951	Y
CAX043502655	38042BP	74	74	74	50	51	50	2,902	Y
CAX043513444	3804190	74	74	74	50	51	50	3,007	Y
CAX043513484	38058XW	74	74	74	50	51	50	2,950	Y
CAX043484286	3804283	74	74	74	50	51	50	2,988	Y
CAX043502729	38042BP	74	74	74	50	51	50	2,949	Y
CAX043502772	3804190	74	74	74	50	51	50	3,173	Y
CAX043502740	38058XW	74	74	74	50	51	50	2,685	Y
CAX043513472	3804283	74	74	74	50	51	50	2,840	Y
CAX043484315	38042BP	74	74	74	50	51	50	2,651	Y
CAX043502671	3804190	74	74	74	50	51	50	2,772	Y

Comments and or exceptions: