

**E321/E323 Print Cartridge**

Printer: E321/E323

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>3000</b>	<b>standard pages</b>
<b>Declared yield value in accordance with ISO/IEC 19752</b>			

**Average** 3974  
**Std Dev** 300  
**90% Lower Confidence** 3818

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

	<b><u>start</u></b>	<b><u>stop</u></b>
<b>Date tested</b>	16-Nov-2004	17-Nov-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At fade 2nd shake At fade
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	8.2.2
Operating system	Windows 2000
Application software	Adobe Acrobat version 6.01
Test page version	IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAD041813512	8803YB4	74	74	74	49	49	48	4,034	Y
CAD041871287	8806BYY	74	74	74	49	49	48	4,312	Y
CAD041892222	8804PZB	74	74	74	49	49	48	3,395	Y
CAD041954704	8804R4B	74	74	74	49	49	48	3,777	Y
CAD041955058	8803YB4	74	74	74	48	49	48	4,209	Y
CAD041812170	8806BYY	74	74	74	48	49	48	4,241	Y
CAD041873150	8804PZB	74	74	74	48	49	48	3,929	Y
CAD041892252	8804R4B	74	74	74	48	49	48	3,927	Y
CAD041892569	8803YB4	74	74	74	48	49	48	4,097	Y
CAD041954961	8806BYY	74	74	74	48	49	48	4,168	Y
CAD041813270	8804PZB	74	74	74	48	49	48	4,155	Y
CAD041871009	8804R4B	74	74	74	48	49	48	3,443	Y

**Comments and or exceptions:**